

WS100-ELECTRONIC

Volumetrics softeners simplex or duplex set with 1" valve mixing



ION EXCHANGE

INDUSTRIAL WATER SOFTENERS

WS100-ELECTRONIC SOFTENERS SIMPLEX OR DUPLEX

- Simplex or duplex volumetrics softeners delivering 6.1m³/h of soft water.
- Electronic controller CI allowing the adjustment of adjustment of all the operating cycles.
- The regeneration is chronometric or volumetric with or without time regeneration lag, and with or without priority of the time on volume.
- From 15 up to 250 liters of resin.



WATER SOFTENERS DELIVERED WITH

- Electronic volumetric valve WS100 with integrated mixing, fitting 1"BSPT, central tubing and strainer.
- Tank(s) in GFR.
- Strong cationic resin.
- Brine tank(s) with grid and overflow (2 brine tanks for duplex).
- Tubing for drain, brine valve, and overflow.
- For Duplex version : Alternating 3 ways electric valve (with mounting kit up to 16" tanks).

APPLICATIONS

- Feed water for steam generators.
- Hot water production.
- Protection of the reverse osmosis systems.
- Process water production
- Any building or industrial application requiring a supply of softened water.

WS100-Electronic Softeners Simplex or Duplex


TECHNICAL SPECIFICATIONS

Liters of resin	Tank	Brine tank volume	Max. flow rate m ³ /h	Exchange capacity °F/m ³					
				Min. 4°F	Salt consumption kg	Medium 5°F	Salt consumption kg	Max. 6°F	Salt consumption kg
15	7 x 35	60	0.75	60	1.20	75	1.80	90	2.85
20	8 x 35	60	1.00	80	1.60	100	2.40	120	3.80
25	9 x 35	100	1.25	100	2.00	125	3.00	150	4.75
30	10 x 35	100	1.5	120	2.40	150	3.60	180	5.70
50	10 x 54	145	2.5	200	4.00	250	6.00	300	9.50
75	13 x 54	200	3.75	300	6.00	375	9.00	450	14.25
100	14 x 65	200	5.00	400	8.00	500	12.00	600	19.00
125	16 x 65	350	6.10	500	10.00	625	15.00	750	23.75
150	16 x 65	350	6.10	600	12.00	750	18.00	900	28.50
175	18 x 65	500	6.10	700	14.00	875	21.00	1050	33.25
200	18 x 65	500	6.10	800	16.00	1000	24.00	1200	38.00
225	21 x 62	500	6.10	900	18.00	1125	27.00	1250	42.75
250	21 x 62	500	6.10	1000	20.00	1250	30.00	1500	47.50

Operating pressure : 2,0 to 8,5 bar

Operating temperature : 4 to 43°C

Connection diameter : 1"



SIMPLEX

ALTERNATE DUPLEX

Liters of resin	DIMENSIONS							
	Tank	Tank + valve			Brine tank			
		Diam (mm)	Height (mm)	Height (mm)	Volume (liters)	Diam (mm)	Diam (mm)	Height (mm)
A	B	C	d	D	E			
15	7 x 35	182	896	190	60	275	390	810
20	8 x 35	207	897	190	60	275	390	810
25	9 x 35	233	898	190	100	330	450	940
30	10 x 35	259	893	190	100	330	450	940
50	10 x 54	259	1381	190	145	380	500	1060
75	13 x 54	335	1398	190	200	430	550	1160
100	14 x 65	369	1674	190	200	430	550	1160
125	16 x 65	413	1705	190	350	475	740	1275
150	16 x 65	413	1705	190	350	475	740	1275
175	18 x 65	559	1721	190	500	575	840	1335
200	18 x 65	559	1721	190	500	575	840	1335
225	21 x 62	559	1721	190	500	575	840	1335
250	21 x 62	559	1721	190	500	575	840	1335



ADH2OC INDUSTRIAL
Headquarters
3, Rue Kercoz
22 220 TRÉGUIER - FRANCE
Tel +33 (0)2 96 40 02 50
Fax +33 (0)2 22 44 98 48
www.adh2oc-industrial.com

Workshop
12 Rue du Plateau - Lieudit «La Vallée Drouard»
28500 CHÉRISY - FRANCE
Tel +33 (0)2 37 50 20 79
Fax +33 (0)2 22 44 98 48
e-mail : infos@adh2oc-industrial.com